



# BIG BATT™

## FIBERGLASS BATT INSULATION



BIG BATT™ fiberglass energy saving insulation can be used in either residential or commercial construction as thermal and acoustic insulation for attics, walls and floors.

The US Department of Energy has found that one of the most cost-effective ways to make your home more comfortable year-round is to add insulation to your attic. Fibertek BIG BATT™ insulation is available in light weight, low and higher density batts, with a large number of sizes that are easily cut to fit around wood or metal trusses and joists. They are easily attached under floors and in vertical spaces by stapling flanges.

Fibertek fiberglass insulation can reduce the average heating and cooling costs of most homes by as much as 20%. BIG BATT™ fiberglass insulation is also available in Foil and FSK facings in all standard sizes and Hi-performance and Cathedral ceiling BIG BATT™ batts are available in R-15, R-21, R-30 and R-38 values. Home owners can save energy, save on home heating and cooling bills and save hard earned money by adding professionally recommended attic, wall and basement insulation. Fiberglass is especially well suited for home use because of its ease of installation, its thermal performance, resistance to mold growth and its non-corrosion of metal such as studs, plumbing and nails etc..

### BIGBATT insulation complies with the following:

#### Unfaced BIGBATT complies with:

- ASTM STANDARD C 665 Type I
- ASTM C 518: Thermal Performance
- ASTM C 1104: Water Vapor Sorption: 5% or less by weight
- ASTM C 1338: pass: Fungi Resistant
- ASTM C 665: Non-Corrosive: 13.8 - pass
- ASTM C 1304: Odor Emmission - pass
- ASTM E 136: Non-combustible - pass
- ASTM E 84: Flame Spread Index: <25
- ASTM E 84: Smoke Developed < 50
- UL® Listed R26642

#### Kraft facing complies with:

- ASTM C 665: Kraft: Type II, Class C Category 1
- ASTM E 96: Water Vapor Permeance Kraft: 1.0 perms
- Kraft: unrated for Flame or Smoke

#### Foil facing complies with:

- ASTM C 553, ASTM C 665: Type III, Class B Category 1
- ASTM E 84: Max. Flame Spread Index: 75
- ASTM E 84: Max. Smoke Developed Index: 150
- ASTM E 96: Water Vapor Permeance: 0.05 perms

#### FSK facing complies with:

- ASTM C 553, ASTM C 665: Type III, Class A Category 1
- ASTM E 84: Max. Flame Spread Index: 25
- ASTM E 84: Max. Smoke Developed Index: 50
- ASTM E 96: Water Vapor Permeance: 0.05 perms

R-VALUE      THICKNESS      SIZES

Contact FiberTEK for the availability of non-standard sizes.

R-VALUE	THICKNESS	SIZES
R-11	3.50"	15"X 93", 15"x 105", 16"X 96", 19"X 48", 19"X 93", 23"x 93", 24"x 48", 24"x 96"
R-13	3.50"	15"X 93", 15"x 105", 16"X 96", 19"X 48", 19"X 93", 23"x 93", 24"x 48", 24"x 96"
R-15	3.50"	15"X 93", 15"x 105", 16"X 96", 23"x 93", 24"x 48", 24"x 96"
R-19	6.25"	15"X 48", 15"X 93", 15"x 105", 16"X 96", 19"X 48", 19"X 93", 23"x 93", 24"x 48", 24"x 96"
R-21	5.50"	15"X 93", 15"x 105", 16"X 96", 23"x 93", 24"x 48", 24"x 96"
R-22	6.50"	15"X 93", 15"x 105", 16"X 96", 19"X 48", 19"X 93", 23"x 93", 24"x 48", 24"x 96"
R-25	8.00"	15"X 93", 15"x 105", 16"X 96", 19"X 48", 19"X 93", 23"x 93", 24"x 48", 24"x 96"
R-30	9.50"	16"X 48", 19"X 48", 24"x 48"
R-30C	8.25"	16"X 48", 24"x 48" (Cathedral ceiling batts)
R-38	12.00"	16"X 48", 24"x 48"
R-38C	10.25"	16"X 48", 24"x 48" (Cathedral ceiling batts)



925 South 4400 West, Salt Lake City, Utah 84104 USA  
 Phone (800) 682 4448 Fax (801) 972 0521  
 info@fibertekinsulation.com  
 www.fibertekinsulation.com



performance fiberglass insulation products